

## Features:

- All components included in one box – do it yourself
- Easily configurable according to consumer need.
- Durable and long-lasting.
- Solar Flood for wide outdoor applications where electrical connection is not possible/difficult.
- Infrared remote controller to dim luminaires with set presets



## TECHNICAL SPECIFICATIONS

### SCOPE OF APPLICATION

- Self-built housing
- Courtyard
- Garage
- Basement
- Store
- Hotel
- Farms

### ALL MODELS

EURO - FLS - 200W
EURO - FLD - 200W
EURO - FLS - 300W
EURO - FLD - 300W
EURO - FLS - 500W
EURO - FLS - 600W

## SOLAR FLOOD LIGHT SERIES

MODEL	Euro-FLS - 200W	Euro-FLD - 200W	Euro-FLS - 300W	Euro-FLD - 300W	Euro-FLS - 500W	Euro-FLS - 600W
Peak Power (PM)	25W	25W	30W	30W	33W	35W
Maximum power Voltage (VMP)	6V	6V	6V	6V	6V	6V
Maximum power Current (IMP)	5A	5A	5A	5A	5.5A	5.38A
Open Circuit Voltage (VOC)	7.2V	7.2V	7.2V	7.2V	7.2V	7.2V
Short Circuit Current (ISC)	5.5A	5.5A	5.5A	5.5A	6A	6.35A
Working Temperature	-15°C To +85°C	-15°C To +85°C	-15°C To +85°C	-15°C To +85°C	-15°C To +85°C	-15°C To +85°C
Tolerance	±5%	±5%	±5%	±5%	±5%	±5%
FLS Light Box Dimension	530x 360 x70 mm	530x 360 x70 mm	610x 360 x100 mm	610x 360 x100 mm	350x 300 x80 mm	360x 310 x60 mm
Solar Panel Box Dimension	N.A	N.A	N.A	N.A	370x 690 x30 mm	370x 640 x30 mm